

GBS SERIES

Briggs Stratton
VANGUARD or INTEK
Gasoline Driven Portable Generator Set

GENPOWER®

GENERATOR

GBS 70M

STANDARD SPECIFICATIONS

Engine

- Type :Vanguard or Intek
- Revoulution: 3000 RPM
- Cooling : Air Cooled
- Electronic Ignition
- Starting System : Recoil

Alternator

- Synchron + brushless
- Number of phase : Monophase
- Excitation : Self excitation
- Power Factor (Cos Ø) : 1
- Insulation class: H / F
- Protection class: IP 21
- Voltage output :Monophase : 230 V
- Frequene : 50 Hz
- Voltage regulation: + % 5

Chassis

- Direct engine-alternator coupling
- Mounted in stainless steel pipe frame
- Vibration absorber wedges between genset chassis
- Engine top fuel tank the with dial type fuel indicator (only on some models)
- Mobilise portable wheels under the chassis
- Canopy (optional)
- Easy lifting and move
- Durable against the environmental effects
- Electrostatic powder painted
- Exhaust silencer protected against environmental effects
- Thermally insulated exhaust system

Control Panel (Standard)

- Voltmeter AC 1 each
- Thermal circuit breaker 1 each
- Outlet socket, with cover and earth contact 2 each



Max. Output Power (KVA)	230 V	6.5
	400 V	-
Frequency	Hz	50
Power Factor	Cos Q	1
Make		Briggs Stratton
Model		Vanguard-Intek
Speed	rpm	3000
Output Power (3600 rpm)	kW (HP)	7,5 (10)
Cylinder Displacement	cm ³	305
Number Of Cylinder		1
Cooling System Type		Air
Initial Start System		Recoil
Fuel Consumption	lt/hr	3.1
Fuel		Gasoline
Oil Capacity	lt	0.8
Fuel Tank Capacity	lt	3.8
Alternator Type		Senkron
Insulation Class		H/F
Protection Class		IP-21
Width	mm	690
Lenght	mm	770
Height	mm	600
Weight	kg	81

TECHNICAL SPECIFICATIONS